
Bike	Suzuki GSX-R 125 / GSX-R 150	**Part No.**	RSI-121
Year	2017-Current	**Fit Kit**	Z039.10618
Notes	Where not supplied use original fittings	**dB Killer**	SCEXDBK42 - (Type MM)

Estimated Fitting Time: 60 Minutes



PLEASE NOTE:

When fitting, start by loosely fitting the headers first, then work towards the back of the bike. Once all components are loosely on the bike, begin to tighten. Starting with the silencer bolts and working towards the front of the bike.

NO.	PART NO.	DESCRIPTION	QTY
1	RSC419	Serket Taper Silencer	1
2	CP972	Header Pipe	1
3	CP973	Connecting Pipe	1
Fit Kit - Z039.10618			
4	Z017.10076	M8 x 40mm Cap Head Bolt	1
5	Z026.20068	Alloy Bolt Finisher	1
6	Z017.10831	M8 x 17mm Washer	1
7	Z017.10062	M8 Nyloc Nut	1
8	Z028.10030	Rubber Coated Spring	3
9	Z028.20385	Double Ended Flute	1

CLASSIFICATION	Closed Circuit Product
HOMOLOGATED	No
DATE	14/05/2024
ISSUE	05
AUTHORISED	G. O'Shea

NOTE: ENSURE SCORPION SYSTEM IS CLEAR OF MOVING PARTS AND ALL ORIGINAL FUNCTIONS WORK CORRECTLY.

Bike	Suzuki GSX-R 125 / GSX-R 150	**Part No.**	RSI-121
Year	2017-Current	**Fit Kit**	Z039.10618
Notes	Where not supplied use original fittings	**dB Killer**	SCEXDBK42 - (Type MM)

Estimated Fitting Time: 60 Minutes



A) Remove original exhaust from bike, taking care to keep all original components in a safe place.

B) Refit Scorpion exhaust as per line diagram above.

C) When fitted take bike for a short ride to ensure all functions are correct.

D) When bike & exhaust are cool enough check all nuts and bolts are still secure.

Thank you for purchasing your Scorpion Silencer.
Care of your exhaust: Please refrain from cleaning silencer with heavy solvents or abrasives!

Vielen Dank Fur den kauf eines Scorpion Schalldampfers! Pflegehinweis: Bitte verwenden Sie niemals Scheuermittel oder aggressive Reiniger zur Pflege Ihres Auspuffes!

Merci d'avoir choisi un echappement Scorpion.
Entretien de votre silencieux: Ne pas utiliser de solvants ou de produits abrasifs!

Muchas gracias por adquirir un Silencioso Scorpion. Le recomendamos no limpiar el silencioso con productos abrasivos o aquellos que contengan disolventes.