
Box: PLOCK 1

BIKE	KAWASAKI ZX-10 R / ZX-10RR / ZX-10R SE	PART NO.	KA-113-CR
YEAR	2016-2020 / 2017-2020 / 2018-2020	FIT KITS	Z039.20570
NOTES	Use standard fittings where not supplied Remove standard gasket if fitted.	FEATURES	This component will fit with O.E and Scorpion Exhaust system.



DO NOT TURN ON BIKE UNTIL INSTALLATION IS COMPLETE AND SERVO WHEEL HAS BE FULLY INSTALLED.

1	Connecting pipe 898
2	55-59mm Clamp (Z016.10004)
3	Servo Disc (Z007.10955)
4	Servo Collar (Z026.20045)
5	M6 Spring Washer (Z017.10027)


NOTE: ENSURE SCORPION SYSTEM IS CLEAR OF MOVING PARTS AND ALL ORIGINAL FUNCTIONS WORK CORRECTLY.

CLASSIFICATION	Closed Circuit Product
HOMOLOGATED	No
ISSUE NO.	03
DATE	03/02/21
AUTHORISED	M.YDLIBI


Box: PLOCK 1


BIKE	KAWASAKI ZX-10 R / ZX-10 RR / ZX-10R SE	PART NO.	KA-113-CR
YEAR	2016-2020 / 2017-2020 / 2018-2020	FIT KITS	Z039.20570
NOTES	Where not supplied use original fittings.	FEATURES	


CONTINUED FROM OVERLEAF:











A) To disconnect cables at the seat end, you have to remove the hexagonal wheel, without turning it's shaft.
Remove bolt in cetre of hexagonal wheel. Support wheel if tight.

B) Remove hexagonal wheel from shaft, retaining O.E bolt. DO NOT TURN SHAFT.
Remove spring clip retaining cables and completely remove the cables.

C) The replacement wheel comes with an aluminium coler that is secured in place with O.E bolt and split washer. TIGHTEN TO 5ft/lb USING A TORQUE WRENCH.

D) The replacment wheel MUST be fitted with the etched letters "UP"

E) The replancement whell will only fit one way with the letters "UP". In case of difficulty please contact us.

WITH SERVO WHEEL FITTED, THE LOOSE CABLES WILL BE REMOVED WITH THE REST OF THE SYSTEM.